



















# Technical Information

CONSTRUCTION: Woven vinyl flooring | COLLECTION: BKB

			 Rolls	 Tiles
<b>Weight:</b>	 EN 430	3.05 kg/m <sup>2</sup>	4.2 kg/m <sup>2</sup>	
<b>Thickness:</b>	 EN 428	2.8 mm	3.4 mm	
<b>Width:</b>	 EN 426	200 cm (6'7")	—	
<b>Roll length:</b>	 EN 426	25 m (approx 82')	—	
<b>Tile dimension:</b>	 EN 427	—	50 x 50 cm <small>16 pcs box / 4 m<sup>2</sup> (19<sup>11/16</sup>" x 19<sup>11/16</sup>")</small>	
<b>Chair with castors:</b>	 EN 985	Pass. >25 000 cycles	Pass. >25 000 cycles	
<b>Impact sound:</b>	 ISO 140-8	ΔLw=15 dB	ΔLw=15 dB	
<b>Dimension stability:</b>	 EN 434	< 0.25%	< 0.25%	
<b>Curling:</b>	 EN 434	< 2 mm	< 2 mm	
<b>Residual indentation:</b>	 EN 433	< 0.2 mm	< 0.2 mm	
<b>Body voltage:</b>	 ISO 1815	< 2 kV	< 2 kV	
<b>Heat flux:</b>	 ISO 8302	0.03 m <sup>2</sup> K/W	0.03 m <sup>2</sup> K/W	
<b>Colour fastness:</b>	 ISO 105-B02	> 6	> 6	
<b>Slip resistance:</b>	 EN 13893 DIN 51130	> 0.3 R9	> 0.3 R9	
<b>Fire rating:</b>	 EN 13501-1 ASTM E 648 ASTM E 662	B <sub>fl</sub> -s1 Class 1 (NFPA 101) 450 or less	B <sub>fl</sub> -s1 Class 1 (NFPA 101) 450 or less	
<b>Classification:</b>	CSTB	U3SP3 NO 12/03 1346	U3SP3 NO 12/03 1347	
<b>Certification:</b>	 EN 14041	No 0402-CPD-419001	No 0402-CPD-419001	

