



















Technical Information

CONSTRUCTION: Woven vinyl flooring | COLLECTION: ETHNIC

			 Rolls	 Tiles
Weight:	 EN 430	3.05 kg/m ²	4.2 kg/m ²	
Thickness:	 EN 428	2.8 mm	3.4 mm	
Width:	 EN 426	200 cm (6'7")	—	
Roll length:	 EN 426	25 m (approx 82')	—	
Tile dimension:	 EN 427	—	50 x 50 cm <small>16 pcs box /4 m² (19^{11/16}" x 19^{11/16}")</small>	
Chair with castors:	 EN 985	Pass. >25 000 cycles	Pass. >25 000 cycles	
Impact sound:	 ISO 140-8	ΔLw=15 dB	ΔLw=15 dB	
Dimension stability:	 EN 434	< 0.25%	< 0.25%	
Curling:	 EN 434	< 2 mm	< 2 mm	
Residual indentation:	 EN 433	< 0.2 mm	< 0.2 mm	
Body voltage:	 ISO 1815	< 2 kV	< 2 kV	
Heat flux:	 ISO 8302	0.03 m ² K/W	0.03 m ² K/W	
Colour fastness:	 ISO 105-B02	> 6	> 6	
Slip resistance:	 EN 13893 DIN 51130	> 0.3 R9	> 0.3 R9	
Fire rating:	 EN 13501-1 ASTM E 648 ASTM E 662	B _{fl} -s1 Class 1 (NFPA 101) 450 or less	B _{fl} -s1 Class 1 (NFPA 101) 450 or less	
Classification:	CSTB	U3SP3 NO 12/03 1346	U3SP3 NO 12/03 1347	
Certification:	 EN 14041	No 0402-CPD-419001	No 0402-CPD-419001	

