

# Technical Information

CONSTRUCTION: Woven vinyl flooring | COLLECTION: LEX



<b>Weight:</b>		EN 430	3.05 kg/m <sup>2</sup>
<b>Thickness:</b>		EN 428	2.8 mm
<b>Width:</b>		EN 426	200 cm (6'7")
<b>Roll length:</b>		EN 426	25 m (approx 82')
<b>Chair with castors:</b>		EN 985	Pass. >25 000 cycles
<b>Impact sound:</b>		ISO 140-8	$\Delta L_w=15$ dB
<b>Dimension stability:</b>		EN 434	< 0.25%
<b>Curling:</b>		EN 434	< 2 mm
<b>Residual indentation:</b>		EN 433	< 0.2 mm
<b>Body voltage:</b>		ISO 1815	< 2 kV
<b>Heat flux:</b>		ISO 8302	0.03 m <sup>2</sup> K/W
<b>Colour fastness:</b>		ISO 105-B02	> 6
<b>Slip resistance:</b>		EN 13893 DIN 51130	> 0.3 R9
<b>Fire rating:</b>		EN 13501-1 ASTM E 648 ASTM E 662	B <sub>fl</sub> -s1 Class 1 (NFPA 101) 450 or less
<b>Classification:</b>		CSTB	U3SP3 NO 12/03 1346
<b>Certification:</b>		EN 14041	No 0402-CPD-419001

