Great appearance and texture at an affordable, unbeatable price

DUNDEE artificial grass by SUMIGRAN offers an unbeatable combination of smart appearance, quality texture and reasonable price. This winning combination is an extremely appealing proposition for our clients and it is another of our star products that beats our competitors hands down. And it is this successful formula of innovative products like DUNDEE which nowadays really singles out SUMIGRAN in the marketplace as a best-in-its-class artificial grass firm in the world today

The fine characteristics of this top product include grass yarn which is 25mm in height, with a density of almost 18,000 stitches /m2 It has 4 colour shades (3 khaki greens and olive mixed with a tanned beige shade)

The curly yarn has been specially treated to increase its volume in order to improve the overall visual appearance of the product, thus giving it a significantly more natural feel. On top of that, it has a more pleasant texture to the touch and for walking on

The monofilament thread is extruded in a flat section with "micro-strips" to reduce shine and reflections on the surface of the product and thus obtaining a more natural finish

We are talking about a product that approaches the barrier of 1,000 gr / m2 of fiber at an extraordinarily competitive price

The DUNDEE grass is one of the most used models in the market for urban landscaping (roundabouts, medians strips, squares, parks, etc.). More and more municipalities trust this product to decorate public areas in their cities



TECHNICAL CHARACTERISTICS OF THE	8500
Filament configuration	8 straight +8 curly
Straight yarn	
Structure	Monofilament
Shape	Micro-strips
Composition	Polyethylene
Colour shade	Two-tone green (two colours)
Matte treatment	Yes
UV stabilised	Yes
Respectful with the environment	Yes, lead and cadmium free
Curly yarn	
Structure	Textured
Composition	Polypropylene
Colour	Beige and green

TECHNICAL CHARACTERISTICS OF THE BACKING		
Primary support composition	Polypropylene	
Primary support layers	1	
Reinforced with net	No	
Primary support weight	135 grammes / m2	
Support coating	Latex	
Support coating weight	800 grammes / m2	

GENERAL TECHNICAL CHARACTERISTICS		
Type of manufacturing system	Tufted cut pile + curly yarn	
Gauge	3/8"	
Stitches per m2	17850 (+/- 10%)	
Stitches rate per 10cm	17 (+/-1)	
Pile height	25 mm (+/- 5%)	
Total height	27 mm (+/- 5%)	
Pile weight	910 gr / m2 (+/- 10%)	
Total weight	1845 gr / m2 (+/- 10%)	
Dimensional stability	+/- 0,60 %	
Water permeability	40 litres / minute / m2	
Installation	Floating without silica sand infill (optional)	

FORMATS AND MEASUREMENTS

DUNDEE



width: 2 meters length: 20 meters















