"Dawn impression"

SUMIGRAN was the pioneer in the sales, marketing and development of the first ever model of artificial grass that did not need sand filling or any repriming accesssory. We were light years ahead of other businesses in a similar industry at the time. The vision we had gave birth to IMPRESSION, which was the first version of our

IMPRESSION artificial grass was actually inspired by Monet's "Dawn Impression" painting. And it too has been a literal revolution, causing a major impact on the artificial grass market just like the work of the French genius did in the art world decades ago


IMPRESSION artificial grass really stands head and shoulders above competing products in the marketplace due mainly to the extraordinary quality of the raw materials used in its manufacture. Its straight yarn consists of a "U" concave shape which boasts magnificent elasticity, resilience and resistance thanks to the polymer

These fibres are 14,000 Dtex of extraordinary quality with a configuration of 8 + 8 filaments per stitch, and guarantees extraordinary resistance to wear and tear. It also has one of the best levels of vertical recovery after being stepped on, in the market today

IMPRESSION artificial grass is designed with a height of 35 mm and a density of 27.300 stitches / m2, these impressive specifications bring it very close to reaching the fibre that exceeds of 2.000 gr / m2, which is an amazingly soft and comfortable product to tread on

There have already been hundreds of thousands of square meters of this special model sold both inside and outside Spain, and the result is always the same story: maximum customer satisfaction and recognition from expert professionals in the sector. We are extremely proud to hear such praise and positive feedback from our customers and this encourages us to continue in our success story of only providing the best, innovative artificial grass products like IMPRESSION. We will strive to continue to enhance our products even more so in the future

IMPRESSION artificial grass - a true work of art right in your garden



TECHNICAL CHARACTERISTICS OF THE YARN		
DTEX	9500	
Filament configuration	8 straight + 8 curly	
Straight yarn		
Structure	Monofilament	
Shape	Concave in U	
Thickness	130 - 150 μm	
Width	0,76 - 0,82 mm	
Composition	Polyethylene	
Colour shade	Two-tone green (two colours)	
Matte treatment	Yes	
UV stabilised	Yes	
Respectful with the environment	Yes, free of lead and cadmium	
Curly yarn		
Structure	Textured	
Composition	Polypropylene	
Colour	Beige and brown	

TECHNICAL CHARACTERISTICS OF THE BACKING		
Primary support composition	Polypropylene	
Primary support layers	1	
Reinforced with net	Yes	
Primary support weight	150 grammes / m2	
Support coating	Latex	
Support coating weight	900 grammes / m2	

GENERAL TECHNICAL CHARACTERISTICS	
Type of manufacturing system	Tufted cut pile + curly yarn
Gauge	3/8"
Stitches per m2	27300 (+/- 10%)
Stitches rate per 10cm	26 (+/-1)
Pile height	35 mm (+/- 5%)
Total height	37 mm (+/- 5%)
Pile weight	2074 gr / m2 (+/- 10%)
Total weight	3124 gr / m2 (+/- 10%)
Dimensional stability	+/- 0,40 %
Water permeability	50 litres / minute / m2
Fire resistance clasification	Efl
Installation	Floating and without silica sand (optional)

FORMATS AND MEASUREMENTS

IMPRESION



width: 2 meters length: 20 meters



width. 4 meters length: 20 meters

















